



# Ledinaire High-bay

## BY021P G2 LED205S/840 PSU WB GR

Ledinaire High-bay - Power supply unit - Beam angle 90° - 90°

The Ledinaire range contains a selection of popular off-the-shelf LED luminaires, each of which come with the high Philips quality levels and competitive price. Reliable, energy-efficient and affordable – just what you need.

### Product data

General Information	
Light source color	840 neutral white
Light source replaceable	Yes
Number of gear units	1 unit
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Optic type	Beam angle 90°
Luminaire light beam spread	90°
Connection	Connection unit 3-pole
Cable	Cable 0.3 m with connector 3-pole
Protection class IEC	Safety class I
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	-
CE mark	CE mark
ENEC mark	-
Warranty period	3 years
Constant light output	No
Number of products on MCB of 16 A type B	6
Photobiological risk	Photobiological risk group 1 @ 200mm to EN62471
EU RoHS compliant	Yes

Service tag	No
Unified glare rating CEN	Not applicable
Operating and Electrical	
Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Initial CLO power consumption	- W
Inrush current	54 A
Inrush time	0.75 ms
Power Factor (Min)	0.9
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Housing Material	Aluminium die-cast ADC1 - alloy grade (EN AC-47100)
Reflector material	Aluminum
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Steel

## Ledinaire High-bay

Optical cover/lens finish	Matte
Overall height	93 mm
Overall diameter	355 mm
Color	Dark gray
Dimensions (Height x Width x Depth)	93 x NaN x NaN mm (3.7 x NaN x NaN in)

### Approval and Application

Ingress protection code	IP65 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [ 1 J]

### Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	20500 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	122 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>80
Initial chromaticity	0.38, 0.38
Initial input power	168 W
Power consumption tolerance	+/-10%

### Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life	7.5 %
50000 h	


Lumen maintenance at median useful life*	L65
50000 h	

### Application Conditions


Ambient temperature range	-20 to +45 °C
Performance ambient temperature Tq	35 °C
Suitable for random switching	No

### Product Data

Full product code	871951452404000
Order product name	BY021P G2 LED205S/840 PSU WB GR
EAN/UPC - Product	8719514524040
Order code	911401642307
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401642307
Net Weight (Piece)	2.450 kg



## Dimensional drawing



### Ledinaire Highbay

