PRODUCT-DETAILS

# E 9F10 GG32

## E 9F10 GG32 Fuse link



### General Information

| | |
|---|---|
| Extended Product Type | E 9F10 GG32 |
| Product ID | 2CSM258713R1801 |
| EAN | 8012542587132 |
| Catalog Description | E 9F10 GG32 Fuse link |
| Long Description | E 9F10 GG32 is a 10,3x38 mm cylindrical fuse for circuit protection |

### Technical

| | |
|---|---|
| Standards | IEC 60269-2 |
| Rated Voltage ($U_r$) | 400 V AC |
| Rated Current ($I_n$) | 32 A |
| Maximum Breaking Capacity | 120 kA |
| Power Loss | at Rated Operating Conditions per Pole 2.8 W |
| Fuse Type | gG |
| Release Type | gG: Used in general protection of cables and lines in installation and industrial applications |
| Construction Material | Ceramic |

© 2024 ABB. All rights reserved.

| | |
|---|---|
| Fuse Size | 10x38 |
| Contact Material | copper silver plated (Cu/Ag) |

## Material Compliance

| | |
|---|---|
| RoHS Information | 9AKK106713A5625 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Date | 27/01/2014 |
| REACH Declaration | 9AKK108467A9482 |
| REACH Information | True - contains substances > 0.1 mass percentage |
| REACH Date | 20240429 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

## Environmental

| | |
|---|---|
| Environmental Information | See RoHS Information |

## Dimensions

| | |
|---|---|
| Product Net Width | 0.001 m |
| Product Net Height | 0.004 m |
| Product Net Depth / Length | 0.001 m |
| Product Net Weight | 0.007 kg |
| Dimension Diagram | 9AKK108466A8532 |

## Ordering

| | |
|---|---|
| Package Level 1 Units | box 10 piece |
| Package Level 1 Gross Weight | 0.075 kg |

## Certificates and Declarations

| | |
|---|---|
| Cut-off Current Characteristic | 9AKK108466A9067 |
| Declaration of Conformity - CE | 9AKK106713A5625 |
| $I^2t$ Characteristic | 9AKK108466A9087 |

## Installation

| | |
|---|---|
| Instructions and Manuals | No document needed |

## Popular Downloads

| | |
|---|---|
| Data Sheet, Technical Information | 9AKK107991A8329 |

© 2024 ABB. All rights reserved.

| | |
|---|---|
| Cut-off Current Characteristic | 9AKK108466A9067 |
| $I^2t$ Characteristic | 9AKK108466A9087 |
| Time-Current Characteristic Curve | 9AKK108467A0144 |

## Classifications

| | |
|---|---|
| ETIM 8 | EC002704 - Cylindrical fuse |
| ETIM 9 | EC002704 - Cylindrical fuse |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 85361050 |
| eClass | V11.0 : 27142002 |
| Object Classification Code | F |

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Protection and Safety Devices → Cylindrical and D0 Fuses





© 2024 ABB. All rights reserved.